

HIGH LIFTING PALLET TRUCKS

SE1056 | Electric/Battery

Compact and easy to operate. Built-in charger, with 70Ah/12V battery as standard that gives many working hours per charging. SE1056 working hours per charging. SE1056 lifts and lowers forks very quickly. PU wheels.

- ELECTRICAL PUMP
- EASY TO USE
- TWO FORK LENGTHS: 1150/1500



Optimal utility for lifting goods to ergonomical working height.

SM1056 | Quick-lift/Manual

World class lifter. High performing lifter with a single lifting cylinder and tall upper part which makes this high lifter very reliable and easy to operate. PU wheels.

- MANUAL PUMP



S1000 | Compact, quick-lift/manual

With a telescopic 2-stage lifting cylinder. Automatic quick lift function up to 150 kg loads, double lifting speed. PU wheels.

- MANUAL PUMP
- TWO FORK LENGTHS: 1150/1500



TECHNICAL INFORMATION

Art.no	Type	Capacity (kg)	Fork width (mm)	Fork length (mm)	Fork height min/max (mm)	Lifting speed (mm/stroke)	Weight (kg)	Steering wheel	Price
S1000	Manual pump	1000	560/160	1150	85-800	18/28	115	PU	
S1000-1500	Manual pump	1000	560/160	1500	85-800	18/28	135	PU	
SM1056	Manual pump	1000	560/160	1190	85-800	12/28	128	PU	
SE1056	Electric pump	1000	560/160	1190	85-800	42/61	158	PU	
SE1056-1500	Electric pump	1000	560/160	1500	85-800	42/61	170	PU	

* Polyurethane wheel = PU

HB1056E-Y | Electric/Battery

Built-in charger, with 70Ah/12V battery as standard that gives many working hours per charging. HB1056E-Y lifts and lowers forks very quickly. PU wheels.

- ELECTRICAL PUMP
- EASY TO USE



HL1000-Y | Quick-lift/manual

Basic high lifting pallet truck with telescopic 2-stage lifting cylinder.

- MANUAL PUMP
- QUICK-LIFT
- TWO FORK LENGTHS: 1150/1500



HB1056M-Y | Quick-lift/manual

Basic high lifting pallet truck with telescopic 1-stage lifting cylinder.

- MANUAL PUMP



SLP10-INOX | Quick-lift/manual

Stainless high lifting pallet truck with 2-stage lifting cylinder.

- MANUAL PUMP



TECHNICAL INFORMATION

Art.no	Type	Capacity (kg)	Fork width (mm)	Fork length (mm)	Fork height min/max (mm)	Lifting speed (mm/stroke)	Weight (kg)	Steering wheel	Price
HB1056E-Y	Electric pump	1000	540/160	1150	85-800	38/65	152	PU	
HB1056M-Y	Manual pump	1000	540/160	1190	85-800	12/28	125	PU	
HL1000-Y	Manual quick lift pump	1000	540/160	1150	85-800	18/28	140	PU	
HL1000-15-Y	Manual quick lift pump	1000	540/160	1500	85-800	18/28	158	PU	
SLP10-INOX	Manual stainless	1000	535/160	1150	85-800	18/28	115	Nylon	

* Polyurethane wheel = PU